

FORMULATED TO BE
"SIMPLY THE BEST"
WATER-BASED PRIMER-SEALER
AVAILABLE ANYWHERE.

PRIMER
All 10[®]

CAMBRIDGE
DEXPOTITE[®]

READ CAREFULLY BEFORE APPLYING.

Primer-All 10[®] is a high-performance, water-based, universal primer, sealer and stain blocker. **Primer-All 10** combines fast-dry convenience with outstanding adhesion and sealing capabilities. **Primer-All 10** can be used for both interior or exterior applications and can be used with either oil/alkyd or latex top coats. When used as an undercoat over new wood, it provides excellent enamel hold-out and will not cause excessive grain raising. Absence of harmful solvents, low odor, and easy clean-up makes **Primer-All 10** a pleasure to use.

DIRECTIONS

SURFACE PREPARATION:

Surface must be completely clean and free from grease, wax, dust, dirt, rust, scaling paint, loose wallpaper or wallpaper paste. If necessary, wash surface with a non-soapy cleaner and allow to dry before priming. If surface is painted, check for unsound paint by cutting an "X" into the paint with a razor. Firmly press tape over the "X" and pull quickly away. If the paint releases, it is unsound and should be removed. Mold-and-mildewed surfaces should be washed with a solution of 3 parts water and 1 part household bleach. Use rubber gloves and eye protection. Glossy surfaces, such as clean glazed ceramic tile and most raw metals, can be primed as is, but deglossing these surfaces by sanding or using deglosser significantly increases the adhesion. Note: maximum hardness and adhesion may take up to 72 hours to develop.

APPLICATION:

Use only with adequate ventilation.
Eye protection is recommended.
Do not take internally.

Stir before using. Apply by brush, pad, roller or with spray equipment. When brushing, flow on with full brush. For spray, thin with water approximately 10%. Do not apply at temperatures below 50°F.

PRODUCT USE:

Primer-All 10 is an ideal prime coat for masonry surfaces, glossy surfaces, ferrous and non-ferrous met-

als, drywall, glass, tile, fiberglass, wood, plywood, brick, pvc, foam, etc. Always allow new masonry to dry a minimum of 1 week before applying **Primer-All 10**. **Primer-All 10** offers excellent adhesion to galvanized metal and very good adhesion to aluminum.

Primer-All 10 eliminates the need for shellac-based primers without the disadvantages. **Primer-All 10** may be used as a fast-dry spot primer on interior/exterior work and may be applied on damp surfaces. If using as a spot primer on repair work, such as spackled drywall or plaster, always use a high quality topcoat to avoid primer bleedthrough.

Primer-All 10 is an excellent multi-purpose stainblocker. It may be used on asphalt, water, rust, crayon, lipstick, felt-tipped marker, food and smoke-damage stains.

In most cases, a single coat will be sufficient; always check any application by only topcoating a small section of the primed surface. If bleedthrough occurs, apply a second primer coat, and repeat topcoating test.

Primer-All 10 will block most tannin stains and rosin bleedthrough spots. However, major variances do occur depending on the wood substrate, and some stains may not be fully sealed.

Primer-All 10 exhibits excellent bleedthrough control on redwood and cedar paneling. In some cases, two primer coats may be required.

Primer-All 10 contains a chalk-binding resin and may be used directly on moderately weathered wood or aluminum siding without cleaning. Always test prime a small section of substrate before priming the entire surface.

Primer-All 10 may be tinted using 2 oz. per gallon of any Universal Colorant. For darker colors, a Deep Tone Base is available.

Note: Some decrease in performance properties may be seen with the addition of colorants.

CLEAN-UP:

Clean brushes and rollers immediately after use; wash in warm water with a mild detergent. Always run mineral spirits through spray equipment after washing to prevent rusting.

COVERAGE:

One gallon will cover approximately 300 square feet of porous masonry surfaces, and up to 450 square feet on smooth non-porous surfaces.

DRYING TIME:

Primer-All 10 will dry in 30 minutes under normal conditions and may be sanded and recoated within one hour. Wait 24 hours before topcoating.

STORAGE:

To avoid skinning, close the container after each use. Keep lid tightly closed during storage. Protect from freezing. If product freezes, allow to thaw to room temperature before use.

MAXIMUM VOC 99.7 g/l (.86 pounds/gallon)

Avoid breathing vapors or spray mist; open doors and windows or use other means to ensure fresh air entry during application and drying. Avoid contact with eyes or repeated/prolonged contact with skin. If you experience headaches, eye-watering or dizziness, increase the flow of fresh air flow, wear eye protection, gloves and/or respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area.

FIRST AID: If swallowed, do not induce vomiting. Call a physician immediately. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water.

For technical assistance, call your Technical Service Representative at 440-786-7185.

HAR ADHESIVES & COATINGS
60 SOUTH PARK
BEDFORD, OHIO 44146